

ISO 9001:2015	Document No: TM/HM/6/525	Version No:0.0	Date effective: ----
Specification of Bearing Flange for Vibration Drive of DUO , CSM & UNI-2S/3S(Part no.DL23.104)			



**RESEARCH DESIGNS AND STANDARDS ORGANISATION
Manak Nagar, Lucknow-226011**

**INFRASTRUCTURE DIRECTORATE
(Track Machines and Monitoring)**

**SPECIFICATION NO.TM/HM/6/525
SPECIFICATION OF BEARING FLANGE FOR VIBRATION DRIVE OF DUO, CSM &
UNI-2S/3S
(Part no.DL23.104)**

DTM-III	EDTM	Page 1 of 3
Prepared By:	Issued By:	

ISO 9001:2015	Document No: TM/HM/6/525	Version No:0.0	Date effective: ----
Specification of Bearing Flange for Vibration Drive of DUO , CSM & UNI-2S/3S(Part no.DL23.104)			

SPECIFICATION NO.TM/HM/6/525

SPECIFICATION OF BEARING FLANGE FOR VIBRATION DRIVE OF DUO, CSM & UNI-2S/3S

(Part no. DL23.104)

- 1.0 Scope:** This specification covers the dimensional, functional and material requirements with testing criteria of Bearing Flange for Vibration Drive of DUO, CSM & UNI-2S/3S machine. This specification may be treated as provisional subject to modifications based on service performance.
- 2.0 Reference documents:** Following documents have been referred to in this specification. Full sets of relevant drawings and the referred codes/specifications, duly incorporating the updated corrections/amendments, shall be available for reference at manufacturer's works.
- i) IS:2062 - 1992 - Steel for general engineering purposes - specification.
 - ii) IS:77-1976 - Linseed oil for paints - specification.
 - iii) RDSO Drg. No. RDSO/TM/15/22 Bearing Flange for Vibration Drive.
- 3.0 Functional requirement:** Bearing Flange is used to mount bearings in vibration shaft assembly of DUO, CSM & UNI-2S/3S tamping machine. All surfaces meant for machining shall be finished as mentioned in the drawing no. RDSO/TM/15/22.
- 4.0 Dimension & Tolerance:** Dimensions and tolerances of Bearing Flange shall be as mentioned in RDSO drawing no. RDSO/TM/15/22.
- 5.0 Material:** The Bearing Flange shall be made from Steel of Grade A or B (Mild Steel) conforming to IS:2062-1992 having minimum tensile strength 410 MPa i.e. 410 N/mm sq. with minimum percentage elongation of 23.
- 6.0 Manufacturing Process:** The Bearing Flange shall be made by either machining from plate/billet of specified material or by forging or machining process.
- 7.0 Marking:** Month and year of manufacture and manufacturer's code / identification shall be engraved / embossed on the non-functioning surface of Bearing Flange.
- 8.0 Inspection and Acceptance Criteria:**
- i) Each components offered by manufacturer shall be checked visually for their surface finish, freedom from defects like porosity, cracks, improper edges etc. Machined surface shall be checked by any suitable pneumatic or electronic equipment.

DTM-III	EDTM	Page 2 of 3
Prepared By:	Issued By:	

ISO 9001:2015	Document No: TM/HM/6/525	Version No:0.0	Date effective: ----
Specification of Bearing Flange for Vibration Drive of DUO , CSM & UNI-2S/3S(Part no.DL23.104)			

- ii) The component found suitable after visual inspection, shall be checked for their dimensions as per relevant drawing.
- iii) Supplier shall produce the certificate that the raw material used for manufacturing of the component conforms to the IS: 2062-1992 as mentioned in Para 5.0.
- iv) Manufacturer shall also produce a test result of chemical property/ analysis report of plate/bar/raw material used for manufacturing of the component.
- v) Any deviations in the test result from the requirement of the specification and drawing shall be the cause of rejection.

9.0 Packing and Protection: Each component shall be protected with one coat of boiled linseed oil conforming to IS: 77-1976 (linseed oil for paint) and shall be packed in card board case.

DTM-III	EDTM	Page 3 of 3
Prepared By:	Issued By:	