

SPECIFICATION No. RDSO/M&C/RP-140/2020 (Revision 2.0)

Government of India
Ministry of Railways

Indian Railway Standard Specification for
Pedestal Liner used on Horn Guides of Bogie
Frame of WDM-4 Locos (Revision 2.0)

M&C Directorate
Research Designs & Standards Organization
Lucknow - 226011

0. FOREWARD

- 0.1 This Specification is issued under fixed Sl. No. RDSO/M&C/RP-140/2020 (Revision 2.0), the final number indicates the year of adoption as standard or in case of revision, the year of last revision.
- 0.2 This specification was first adopted in year 1984 and has been revised mainly for incorporating quality control practices. A code of practice for quality control and inspection of rubber and plastic components (Appendix 'A') is incorporated to ensure satisfactory process and quality control at the works of the manufacturers.
- 0.3 This specification is intended to cover the technical provisions relating to materials, constructions and tests, and does not include all the necessary provisions of the contracts.
- 0.4 For the purpose of deciding whether a particular requirement of this standard is complied with, the final value observed on calculated, expressing the result of a test or analysis, shall be rounded as per IS:2:1960 (Reaffirmed 2016). The number of significant places retained in the rounded off value should be the same as that of the specified value in this standard.
- 0.5 The specification contained a code of practice for quality control and inspection of rubber and plastic component (Appendix 'A') to ensure satisfactory process and quality control at the works of the manufacture. The provision of this code shall be applicable for all the rubber & plastic components being used in the railways.

1.0 SCOPE

This specification prescribes the requirements and method of tests for plastic pedestal liner used on Horn guides of bogie frame of WDM4 locos. The liner is subjected to compressive and sliding forces against the axle box steel liner under ambient temperature up to 60°C. The liner shall be of self-lubricating type having low coefficient of friction and shall have dimensional stability and high impact strength.

2. REQUIREMENTS

2.1 Material

The material used for the manufacture of liner shall be Molybdenum disulphide filled nylon (minimum 1.2% by weight) and suitably compounded so as to conform to the requirements stipulated in this specification.

2.1.1 The

2.2 Construction

The liner shall be manufactured either by injection moulding or by casting or extrusion as per the relevant drawing and shall be smooth, free from voids, splash marks, crazing and any other moulding defects.

3. TESTS

3.1 Note: The tests given in Table I shall be conducted on “as moulded specimens”.

“As moulded specimens” are defined as those which, upon immediate removal from the mould, are sealed in containers impermeable to moisture/water vapour. The tests shall be carried out on the finished product or from the prepared test specimens as per the method of each test indicated in the Table I, using the same compound and moulding techniques.

TABLE I

S. No	Properties	Values	Test Method
1.	Specific gravity	1.14-1.16	ASTM D 792
2.	Hardness (Rockwell-R), min	115	-
3.	Tensile strength (MPa), min	85	ASTM D 638
4.	Elongation at break (%)	40-80	ASTM D 638
5.	Compressive strength (MPa), min	100	ASTM D 695
6.	Water absorption (%) at 27 ± 1°C for 24 hrs.	1-2	ASTM D 570

3.2 Conditioning

3.2.1 The liners shall be conditioned by immersing in hot water above 80°C so as to achieve the amount of water absorbed not less than 2.5% by weight.

4. MARKING

- 4.1 Each liner shall be legibly embossed in 3 mm letters with manufacturer's initial/trade mark, part number and last two digits of the year of manufacture.

5. SAMPLING AND CRITERIA FOR CONFORMITY

- 5.1 A minimum of six test samples or 0.5% of the lot offered for inspection whichever is more shall be drawn for the tests indicated in the specification. Should any of the test samples fail to meet the requirements an additional two sets of samples from the same lot shall be drawn for retesting. Should any of the retest samples fail to meet the requirements, the entire lot shall be rejected.
- 5.2 In the event of the rejection of the entire lot, after the retest of samples, the entire lot offered for inspection shall be made unusable, in the presence of the Inspecting Officer/Purchaser.

6. PACKING

- 6.1 The liner shall be packed in stout wooden boxes so as to avoid damage during transit.

7. STORAGE

- 7.1 The rubber tube shall be stored in a cool dry place, in their original packing.

8. "Firm should comply Make in India policy and Public Procurement (Preference to Make in India) order -2017 under this specification" and subsequent amendment done time to time.

APPENDIX 'A'

CODE OF PRACTICE FOR QUALITY CONTROL AND INSPECTION OF RUBBER
AND PLASTIC COMPONENTS

A.1 THE SYSTEM

A.2 RECORDS, TESTS & SAMPLING:

A.2.1 The manufacturer shall furnish the Purchasing/Inspecting authorities the detail of tests and inspection records and other relevant records as required under the quality control systems in force. These records and reports shall be maintained by the Competent Technical Authority of the manufacturers and shall be open to examine by the Purchasing/Inspecting authorities at all reasonable time. The Purchasing/Inspecting authorities at their discretion may draw samples of materials used in manufacture and products at any stage of production for conforming tests either at the works of the manufacturers or in an approved laboratory. In case the samples do not conform to the requirements of the specification double the number of samples from the same lot/batch shall be drawn for re-tests. Should any one of the re-test a sample does not conform to the requirements, the entire lot/batch shall be rejected.

A.2.2 The manufacturer shall supply and submit all gauges for the approval of the Inspecting Officer.

A.2.3 All tests required by the Inspecting Officer shall be carried out in his presence and he shall be supplied with a copy of the results signed by the manufacturer or his representative.

A.2.4 The manufacturer shall furnish the material for all tests required and shall also provide the necessary labour and appliances for carrying out such tests. Failing facilities at his own works, the tests shall be carried out at a testing works approved by the Purchaser at the expense of the manufacturer.

A.2.5 The liners shall be supplied to the purchaser when requested, free of cost for testing.

A.2.6 The liners found to be defective in any way after delivery may be returned to the manufacturer at his own expense notwithstanding the fact that they may have passed the tests prescribed by the specification and have been accepted by the Inspecting Officer.

A.2.7 The notice shall be given to the Inspecting Officer when the components are ready for inspection.

A.2.8 The liners shall not be dispatched from the manufacturer's works before an acceptance certificate has been obtained from the Inspecting Officer.

A.3 APPROVED MANUFACTURERS:

A.3.1 The manufacturer should have complete manufacturing and quality control facilities as per the specification at their works.

A.3.2 For reasonable quality assurance, it is desirable that the components are procured from manufacturers approved by Research Designs & Standards Organization (RDSO), Lucknow or by any other agency as assigned by the Purchasing Authority, based on evaluation of the components as per the specification, manufacturing and quality control facilities and quality assurance programme. However, such approval does not guarantee the supply of consistent quality of material/components and therefore every lot offered shall be subjected to inspection and testing as per the specification.

A.3.3 The approved manufacturers shall be subjected to periodical re-appraisal (periodicity for each component shall be assigned by the approving authority). In case of withdrawal of any manufacturing and quality control facilities provided at the time of approval of the component produced at the time of re-appraisal are not conforming to the specification, the manufacturers are liable to be withdrawn from the approved list. The approving authority reserves the right to withdraw the manufacturers from the approved list without assigning any reason.

A.3.4 The consignee may also periodically arrange testing if so desired, at RDSO or in an approved laboratory for confirmatory tests within six months from the date of receipt of the supplies, in their original packing. In case of samples do not conform to the specification, the consignee may at their discretion suspend the manufacturer for further supply and the fact brought to the notice of approving/inspecting authorities for appropriate action.
