

RESEARCH DESIGNS AND STANDARDS ORGANISATION Manak Nagar, Lucknow-226011

Track Machine and Monitoring Directorate

SPECIFICATION NO.TM/HM/6/511 SPECIFICATION OF BEARING BUSH FOR DISTRIBUTOR GEAR OF CSM, UNIMAT & T-EXP (Part no.UD64.906)

DTM-III	EDTM	Page 1 of 3
Prepared By:	Issued By:	

ISO 9001:2015	Document No: TM/HM/6/511	Version No:0.0	Date effective: 07/03/2022
Specification of Bearing bush for distributor gear of CSM LINIMAT & T-Exp (Part no LID64 906)			

SPECIFICATION NO.TM/HM/6/511

SPECIFICATION OF BEARING BUSH FOR DISTRIBUTOR GEAR OF CSM, UNIMAT & T-EXP (Part no.UD64.906)

- **1.0 Scope**: This specification covers the dimensional, functional and material requirements with testing criteria of bearing bush for distributor gear. This specification may be treated as provisional subject to modifications based on service performance.
- **2.0 Reference documents:** Following documents have been referred to in this specification. Full sets of relevant drawings and the referred codes/ specifications, duly incorporating the updated corrections/amendments, shall be available for reference at manufacturer's works.
 - i) IS:2062 1992 Steel for general engineering purposes specification.
 - ii) IS:77-1976 Linseed oil for paints specification.
 - iii) RDSO Drg. No. RDSO/TM/27/21 bearing bush for distributor gear.
- **3.0 Functional requirement:** The bearing bush for distributor gear shall be capable to hold the vibration motor of tamping unit and provide torque to rotate the vibration shaft. All surfaces meant for machining shall be finished as mentioned in the drawing no. RDSO/TM/27/21.
- **4.0 Dimension & Tolerance:** Dimensions and tolerances of the bearing bush for distributor gear shall be as mentioned in RDSO drawing no. RDSO/TM/27/21.
- **5.0 Material:** The bearing bush for distributor gear shall be made from Steel of Grade A or B (Mild Steel) conforming to IS:2062-1992 having minimum tensile strength 410 MPa i.e. 410 N/mm² with minimum percentage elongation of 23.
- **Manufacturing Process:** Bearing bush for distributor gear shall be made by either machining from billet/bar of specified material or by forging or machining process.
- **7.0 Marking:** Month and year of manufacture and manufacturer's code / identification shall be engraved / embossed on the non-functioning surface of the bearing bush for distributor gear.

DTM-III	EDTM	Page 2 of 3
Prepared By:	Issued By:	

ISO 9001:2015	Document No: TM/HM/6/511	Version No:0.0	Date effective: 07/03/2022
Specification of Bearing bush for distributor gear of CSM UNIMAT & T-Exp (Part no UD64 906)			

8.0 Inspection and Acceptance Criteria:

- i) Each components offered by manufacturer shall be checked visually for their surface finish, freedom from defects like porosity, cracks, improper edges etc. Machined surface shall be checked by any suitable pneumatic or electronic equipment.
- ii) The component found suitable after visual inspection, shall be checked for their dimensions as per relevant drawing.
- iii) Supplier shall produce the certificate that the raw material used for manufacturing of the component conforms to the IS: 2062-1992 as mentioned in Para 5.0.
- iv) Manufacturer shall also produce a test result of chemical property/ analysis report of raw material used for manufacturing of the component.
- v) Any deviations in the test result from the requirement of the specification and drawing shall be the cause of rejection.
- **9.0** Packing and Protection: Each component shall be protected with one coat of boiled linseed oil conforming to IS:77-1976 (linseed oil for paint) and shall be packed in card board case.

DTM-III	EDTM	Page 3 of 3
Prepared By:	Issued By:	