

भारत सरकार-रेल मंत्रालय
रेलपथ मशीन एवं मॉनीटरिंग निदेशालय
अनुसंधान अभिकल्प और मानक संगठन
लखनऊ- 226011
Telefax:0522-2453857



Government of India-Ministry of Railways
Track Machine & Monitoring Directorate
Research Designs & Standards Organisation
Lucknow- 226011
Email : dtm3rds@gmail.com

सं० : टीएम/एचएम/1 खंड-2
No. TM/HM/1 Vol.II

दिनांक : 06.12.2017
Dated: 06.12.2017

By Regd. Post

मुख्य अभियन्ता (ट्रैक मशीन)

मध्य रेलवे, सीएसटी, मुंबई-400 001
पूर्व रेलवे, फेयरली प्लेस, कोलकाता-700 001
पूर्व मध्य रेलवे, हाजीपुर-844 101
पूर्व तट रेलवे, रेल विहार, चन्द्रशेखरपुर, मुवनेश्वर-751023

उत्तर रेलवे, बड़ीदा हाउस, नयी दिल्ली-110 001
उत्तर मध्य रेलवे, महा प्रबन्धक कार्यालय,
सुबेदारगंज, इलाहाबाद-211003

उत्तरपूर्व रेलवे, गोरखपुर 273012
उत्तर पूर्व सीमान्त रेलवे, मालीगांव, गुवाहाटी-781 011
उत्तर पश्चिम रेलवे, जयपुर-302 001
दक्षिण रेलवे, पार्क टाउन, चेन्नई-600 003
दक्षिण मध्य रेलवे, रेल निलायम, सिकन्दराबाद-500 071
दक्षिण पूर्व रेलवे, गार्डन रीच, कोलकाता-700 043
दक्षिण पूर्व मध्य रेलवे, बिलासपुर-495 004
दक्षिण पश्चिम रेलवे, हुबली-580 023
पश्चिम रेलवे, चर्चगेट, मुंबई-400 020
पश्चिम मध्य रेलवे, जबलपुर-482 001

उप मुख्य अभियन्ता (ट्रैक मशीन)

सी.पी.ओ.एच. कार्यशाला पो० धूमनगंज
इलाहाबाद-221012
सी.पी.ओ.एच. कार्यशाला दक्षिण मध्य रेलवे,
रायनापाडु, विजयवाडा, जिला कृष्णा, आन्ध्र प्रदेश. 521241

Chief Engineer (Track Machines)

C R, CST Mumbai - 400 001.
E R, Fairlie Place, Kolkata-700 001.
E C R, Hazipur-844 101
East Coast Rly, Rail Vihar Chandrashekhar Pur
Bhubaneshwar-751023
N R, Baroda House, New Delhi-110 001.
NCR, GM Office Subedarganj Allahabad-211003

N E R, Gorakhpur-273 012.
N F R, Maligaon, Guwahati -781 011.
N W R, Jaipur-302 001.
S R, Park Town, Chennai -600 003.
SCR, Rail Nilayam, Secunderabad-500 071.
S E R, Garden Reach, Kolkata-700 043.
South East Central Rly, Bilaspur-495 004
SWR, Hubli-580 023
W R, Churchgate Mumbai-400 020
WCR, Jabalpur-482 001

Dy. Chief Engineer (Track Machines)

C.P.O.H. Workshop, N.C. Railway,
P.O. Dhoomanganj Allahabad-221012
C.P.O.H. Workshop, S.C. Railway,
Rayanapadu, Vijawara, Distt.-Krishna, Andhra
Pradesh, Pin code -521241 .

Sub: Guidelines regarding painting of Track Machines.

Guidelines regarding painting of Track Machines are being incorporated in recently revised specification of Track Machines like BCM, High Output BCM, BRM, UTV etc. The same should be followed for all the Track Machines during overhauling/repairs/refurbishing etc. The Guidelines regarding painting of Track Machines is enclosed herewith for adoption in All Zonal Railways and the same is uploaded on RDSO website at following address www.rds.gov.in → Directorates → Track Machine and Monitoring Directorate → Guidelines/Instructions.

DA-As above.


06.12.17

(ओम प्रकाश)
निदेशक / टीएम-3
(Om Prakash)
Director/TM-III

GUIDELINES FOR PAINTING OF TRACK MACHINES:

- 1.0 The machine body shall be painted in golden yellow colour of Indian Standard Colour code of 356 as per IS:5 The exterior painting shall be polyurethane binder based conforming to RDSO Specification No. M&C/PCN/100/2013 (Specification for Epoxy cum Polyurethane Painting System –Two packs for the Exterior Painting of Railway Coaches, Diesel and Electric Locomotives and other Industrial Applications) or ISO 12944.
- 1.1 Following should be written in black on the machine generally at the following location in English & Hindi.
 - 1.1.1 Indian Railways logo of height between 300 mm to 600 mm as suitable on all four faces of the machine.
 - 1.1.2 The text " INDIAN RAILWAYS" shall be written in Bold and in Black colour of size equal to or slightly smaller than the size of logo but of size not less than 250 mm on both side faces and below the Indian Railways logo.
 - 1.1.3 Machine model and manufacturing Year shall be written in black colour and in letter of size less than the size in which Indian Railways is written but not less than 200 mm in any case below the text "INDIAN RAILWAYS" mentioned above.
 - 1.1.4 If required, the Manufacturers Name may be written in size not more than 150 mm and should not be at more than four locations. Also the Manufacturers Logo may be provided at not more than two Locations and should be of size less than 200mm.

Note: If, there is insufficient space for writing the above mentioned matter at the prescribed locations, railway official may decide to write the same at suitable, locations appropriate for a particular type/model of machine.